

3M™ Aluminium Foil Tape 1436 & 1436P



Product description

An aluminium foil combined with a rubber adhesive and an easy release liner designed for holding and sealing on a variety of surfaces. 1436 and 1436P meet low flammability rating according to DIN 4102B1.

- Foil backing provides reflective surface for both heat and light.
- Rubber adhesive bonds to many surfaces.
- Low water vapor transmission rate offers good sealing and patching performance.
- Best results obtained when applied to clean dry surfaces above 0 °C.
- Performance range is from -25 °C to +70 °C; short term up to 100 °C.



Physical properties

	1436	1436P
Adhesive type	Synthetic Rubber	
Backing	Soft Aluminium	
Backing Thickness	0,025 mm	
Total Tape Thickness (without liner)	0,065 mm	
Liner	0,055 mm siliconized glassine white paper liner	0,065 mm siliconized white paper liner



Typical performance characteristics

Property	Values
Adhesion to steel after 72 hour dwell at room temperature according to AFERA 5001	9,5 N / 10 mm
Tensile strength according to AFERA 4005	18 N / 10 mm
Elongation at break according to AFERA 4005	6%
Water vapour transmission Rate	< 1.0 g/m ² x 24 h
Flammability rating according to DIN 4102 <small>Reference PA-111 2-216</small>	B1
Fire protection class acc. to EN 45545-2/2016 <small>Reference 2000488</small>	R1 / HL3; R7 / HL3



Storage and shelf life

- Store in the original packaging.
- Avoid direct sunlight and other UV-light and heat sources.
- Ideal conditions are 20 °C and 50% relative humidity

If stored properly, product retains its performance and properties for 12 months from the date of manufacturing.

Further technical data

3M can offer extended data for different test conditions and substrates. Please get in touch with your 3M Sales Rep or Application Engineer.

Trademarks: 3M is a trademark of 3M Company.

For additional information: To request additional product information or to arrange for sales assistance, please contact your local 3M organization.

Automotive Applications: This product is an industrial product and has not been designed or tested for use in certain automotive applications, including, but not limited to, automotive electric powertrain battery or high voltage applications. This product does not fully adhere to typical automotive design or quality system requirements, such as IATF 16949 or VDA 6.3. This product may not be manufactured in an IATF certified facility and may not meet a Ppk of 1.33 for all properties. The product may not undergo an automotive production part approval process (PPAP). Customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's automotive application and for conducting incoming inspections before use of the product. Failure to do so may result in injury, death, and/or harm to property. No written or verbal statement, report, data or recommendation by 3M related to automotive use of the product shall have any force or effect unless in an agreement signed by a 3M Vice President of Research & Development. Customer assumes all responsibility and risk if customer chooses to use this product in an automotive electric powertrain battery or high voltage application, and 3M will not be liable for any loss or damage arising from or related to the 3M product or customer's use of the product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity or recall costs), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability. In no event shall 3M be liable for any damages in excess of the purchase price paid for the product. NOTWITHSTANDING ANY OTHER STATEMENT TO THE CONTRARY, 3M MAKES NO REPRESENTATIONS, WARRANTIES OR CONDITIONS WHATSOEVER, EXPRESS OR IMPLIED, REGARDING THE PRODUCT IF USED IN AN AUTOMOTIVE ELECTRIC POWERTRAIN BATTERY OR HIGH VOLTAGE APPLICATION, INCLUDING, BUT NOT LIMITED TO, ANY WARRANTY ON PERFORMANCE, LONGEVITY, SUITABILITY, COMPATIBILITY, OR INTEROPERABILITY, OR ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE.

Important notice: All statements, technical information and recommendations contained in this document are based upon tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method or application. All questions of liability relating to this product are governed by the terms of the sale subject, where applicable, to the prevailing law.

Values presented have been determined by standard test methods and are average values not to be used for specification purposes.

Our recommendations on the use of our products are based on tests believed to be reliable but we would ask that you conduct your own tests to determine their suitability for your applications. This is because 3M cannot accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations.