



3M™ PELTOR™ TEP-300 EU Tactical Earplug

Product Description

3M™ PELTOR™ Tactical Earplugs, TEP-300 features environmental listening function – a capability designed to help provide auditory situational awareness, while still helping provide protection from hazardous noise.

Key Features

- Intuitive one-button operation
- Rechargeable
- Portable charging compartment
- Replaceable communications eartips
- Environmental Microphone Port
- IP68 Water and Dust Resistant
- Near Field Magnetic Induction (NFMi) - Wireless connection to 3M™ PELTOR™ System control Units, SCU-300
- In Ear Speech Microphone
- Micro USB-C Charging Port



Applications

The small size makes 3M™ PELTOR™ Tactical Earplug compatible with most headborne Personal Protective Equipment (PPE) such as helmets, eye wear, and respirators.

Standards and Approvals

Hereby, 3M Svenska AB declares that the product is in compliance with appropriate directives or regulations to fulfill the requirements for the CE marking. The full text of the EU declaration of conformity is available at the following internet address: www.3M.com/PELTOR/DOC.

A copy of the declaration of conformity and additional information required in the directives or regulations can also be obtained by contacting 3M in the country of purchase.



Near Field Magnetic Induction



Hearing protection with level-dependent function for ambient listening

Approvals

PPE Regulation 2016/425
EMC Directive 2014/30/EU
ROHS Directive 2011/65/EU
Radio Directive 2014/30/EU
RED Directive 2014/53/EU

Military Approvals

Tested according to the applicable parts of MIL-STD-810G, EMC-MIL-STD-461G.

Environmental Performance:

Tested in accordance with MIL-STD-810G

Models:

Part Number	Description	Legacy 3M ID	SAP ID	Color
TEP-300 EU CY	3M™ PELTOR™ Tactical Earplug, TEP-300 CY, Coyote Brown	70-0717-3430-8	7100227628	
TEP-300 EU GE	3M™ PELTOR™ Tactical Earplug, TEP-300 GE, Grey	70-0717-3427-4	7100227651	
TEP-300 EU TN	3M™ PELTOR™ Tactical Earplug, TEP-300 TN, Tan	70-0717-3426-6	7100227629	

Accessories and Spare parts

Part number	Description	Legacy 3M ID	SAP ID
TEP-300R CY	3M™ PELTOR™ Replacement Earplug, TEP-300R CY, Right, Coyote Brown	70-0717-3433-2	7100227632
TEP-300L CY	3M™ PELTOR™ Replacement Earplug, TEP-300L CY, Left, Coyote Brown	70-0717-3441-5	7100227644
TEP-300R TN	3M™ PELTOR™ Replacement Earplug, TEP-300R TN, Right, Tan	70-0717-3440-7	7100227649
TEP-300L TN	3M™ PELTOR™ Replacement Earplug, TEP-300L TN, Left, Tan	70-0717-3439-9	7100227647
TEP-300R GE	3M™ PELTOR™ Replacement Earplug, TEP-300R GE, Right, Grey	70-0717-3438-1	7100227648
TEP-300L GE	3M™ PELTOR™ Replacement Earplug, TEP-300L GE, Left, Grey	70-0717-3437-3	7100227645
TEP-300C GE	3M™ PELTOR™ Replacement Case, TEP-300C GE, Grey	70-0717-3436-5	7100227638
TEP-300C CY	3M™ PELTOR™ Replacement Case, TEP-300C CY, Coyote Brown	70-0717-3435-7	7100227630



Accessories and Spare parts

Part number	Description	Legacy 3M ID	SAP ID
TEP-300AD	3M™ PELTOR™ TEP-300AD, Battery adapter AAA	70-0717-3434-0	7100227631
CCC-GRM-25	3M™ PELTOR™ Communication Tip, Triple C, 25 pairs	70-0716-7521-2	7100103087
370-TEPL-25	3M™ UltraFit Communication Tips Replacement, Large, 25 pairs	70-0716-7374-6	7100066388
370-TEPM-25	3M™ UltraFit™ Communication Tips Replacement, Medium, 25 pairs	70-0716-7373-8	7100066387
370-TEPS-25	3M™ UltraFit™ Communication Tips Replacement, Small, 25 pairs	70-0716-7372-0	7100066371
PELTIP5-01	3M™ Torque™ Eartips, 50 pairs	XH0011679626	7000108492
TEP-CORD	3M™ LEP/TEP/EEP Cord	70-0716-7379-5	7100074090

Technical Specifications

Speech Microphone Type:

In Ear

Power / Electrical Characteristics:

Earplug Battery Type:	Lithium Ion
Operating time:	Approximately 10 hours
Earplug Battery Charge Time:	Approximately 60 minutes
Case Battery Type:	3 AA or AAA Alkaline Batteries (with adapter)
Case Battery Life:	Up to 16 recharging cycles with AA batteries
Case USB Type:	Micro C 3.1

Near Field Magnetic Induction (NFMI):

Transmission rate:	596 kbit/s
Range:	approximately 50 cm (20 in)
Frequency:	9.8 - 11.7Mhz

Physical Characteristics:

Case Size (L x W x H):	114.2 mm x 78.2 mm x 29 mm
Case Material:	ABS
Weight Charger with batteries, 2 earpieces:	188 g
Weight Charger:	104 g
Weight 1 earplug:	4,7 g

Environmental Characteristics:

Earpiece operating temp:	-20 to +50°C
Charger operating temp:	0 to +45°C
Shelf Life:	Max 12 months
Waterproof Rating :	Earpiece and Case (with lid and USB port securely closed) are IP68 compliant

Recommended Storage Conditions (<90% humidity):

1 year:	-20 to +20°C
3 months:	-20 to +45°C
1 month:	-20 to +60°C

User limitation: Never modify or alter this product

Laboratory Attenuation Values*** EN 352-2:2002

3M™ PELTOR™ CCC-GRM-25 Communication Eartips

Frequency (Hz) ²	125	250	500	1000	2000	4000	8000
Mean Attenuation (dB) ³	35.1	32.5	37.5	37.9	37.1	40.8	44.6
Standard Deviation (dB) ⁴	5.5	4.9	5.1	4.8	4.3	4.6	4.7
Assumed Protection Value (dB) ⁵	29.6	27.6	32.3	33.2	32.9	36.2	39.9

SNR=35 dB H=34 dB M=33 dB L=31 dB

3M™ Torque™ Communication Eartips

Frequency (Hz) ²	125	250	500	1000	2000	4000	8000
Mean Attenuation (dB) ³	38.1	35.5	40.7	40.9	37.5	40.3	44.9
Standard Deviation (dB) ⁴	5.4	5.4	5.7	5.8	3.2	3.3	4.2
Assumed Protection Value (dB) ⁵	32.7	30.1	35.0	35.1	34.3	37.0	40.7

SNR=37 dB H=36 dB M=35 dB L=33 dB

3M™ UltraFit™ Communication Eartips

Frequency (Hz) ²	125	250	500	1000	2000	4000	8000
Mean Attenuation (dB) ³	32.8	30.2	31.6	31.2	33.0	34.4	37.9
Standard Deviation (dB) ⁴	6.2	4.5	5.4	4.4	4.0	4.8	3.9
Assumed Protection Value (dB) ⁵	26.5	25.7	26.2	26.8	29.0	29.6	34.0

SNR=30 dB H=29 dB M=27 dB L=27 dB

***3M strongly recommends personal fit testing of hearing protectors. Research suggests that users may receive less noise reduction than indicated by the attenuation label value(s) on the packaging due to variation in fit, fitting skill, and motivation of the user. Refer to applicable regulations for guidance on how to adjust attenuation label values. In the absence of applicable regulations, it is recommended that the SNR be reduced to better estimate typical workplace protection.

WARNING: 3M strongly recommends personal fit testing of hearing protectors. Research suggests that users may receive less noise reduction than indicated by the attenuation label value(s) on the packaging due to variation in fit, fitting skill, and motivation of the user. Refer to applicable regulations for guidance on how to adjust attenuation label values. In the absence of applicable regulations, it is recommended that the SNR be reduced to better estimate typical protection.

In the box

1x TEP-300**	2x 3M™ UltraFit Communication Tips Replacement, Small
2x AA batteries	2x 3M™ Torque™/Skull Screw Eartips
1x user Instruction	2x 3M™ PELTOR™ Communication Tip, Triple C
2x 3M™ UltraFit Communication Tips Replacement, Large	1x 3M™ PELTOR™ TEP-300AD, Battery adapter AAA
2x 3M™ UltraFit Communication Tips Replacement, Medium	



3M Personal Safety Division

3M Svenska AB, Box 2341
SE-331 02 Värnamo
Sweden
Internet: www.3M.com
Email: cstechservice@mmm.com
Phone: +46 (0)370-65 65 00

3M PSD products are for occupational use only. Please recycle. Printed in Sweden. © 3M 2020. All rights reserved. The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by 3M Company is under license. 3M, PELTOR and ComTac are trademarks of 3M Company, used under license in Canada.

3M acknowledges the respective Trademark Owners' rights in this literature.

Warranty:

The warranty does not cover any damage caused by neglected maintenance or careless handling. For more information on maintenance, please see the user instruction. For complete warranty condition, contact your dealer or local 3M office

Important Notice

3M does not accept liability of any kind, be it direct or consequential (including, but not limited to, loss of profits, business and/or goodwill) arising from reliance upon any information herein provided by 3M. The user is responsible for determining the suitability of the products for their intended use. Nothing in this statement will be deemed to exclude or restrict 3M's liability for death or personal injury arising from its negligence.