

Cappture™ ANSI • CE • CSA •



DIELECTRIC

Dielectric // Fits over most prescription glasses // Temples extend from browbar to avoid interference with prescription frame's temples // Custom imprinting available

Lens and Temples | 4 Variations

- ES9910ST ● ● Clear **H2X** AF
- ES9910STM ● ● Clear **H2MAX** AF
- ES9920ST ● ● Gray **H2X** AF
- ES9920STM ● ● Gray **H2MAX** AF



**WATCH THE
CAPPTURE
VIDEO**



Part No.	Lens Marking	Temple Marking	General Specifications	Materials
ES9910ST	2C-1.2 P 1FT N CE	CE P EN166 FT	Weight: 29.5 gm	Lens: polycarbonate
ES9910STM	2C-1.2 P 1FT KN CE	CE P EN166 FT	Bridge: 23.1 mm	Nosepiece: polycarbonate
ES9920ST	5-2.5 P 1FT N CE	CE P EN166 FT	Lens base: 2.5 curve	Temple: polycarbonate
ES9920STM	5-2.5 P 1FT KN CE	CE P EN166 FT	Lens size diagonal: 145.7 mm	Hinge: polycarbonate
			Lens size vertical: 51.5 mm	
			Lens thickness: 1.8 mm	
			Overall length: 160 mm	
			Overall width: 132.5 mm	

Lens Marking Symbols

Code - field of use

2 or 3: UV filter
5 or 6: Solar filter

Colour Perception

C: Unimpaired colour perception

Protection Class

1.2 - 6: Degree of visible light filtration

Optical Class

1: High optical quality - no optical distortion

Mechanical Strength

F: Low energy impact, resists a 6 mm, .86 g at 45 m/s

T: Impact protection at extreme temperature conditions

Symbols

P: Manufacturer's mark
K: Resistance to surface damage by fine particles
N: Filter with anti-fog
CE: Europe standard

Temple Marking Symbols

Symbols

CE: Europe standard
P: Manufacturer's mark
EN166: CE specification for protective eyewear

Mechanical Strength

F: Low energy impact
T: Impact protection at extreme temperature conditions