

Cortez® ANSI CE



CO-INJECTED
TEMPLES



RUBBER
NOSEPIECE

Durable co-injected temples

Ribbed cushioned nosepiece

Part No.	Black Temples
ESB3610S ●●	Clear
ESB3610ST ●●	AF Clear H2X
ESB3620S ●●	Gray
ESB3620ST ●●	Gray H2X



There's more to see at
PYRAMEXSAFETY.COM

(P) +44 (0) 1635 254220 | (E) info@pyramexeurope.com

All safety eyewear meets ANSI Z87.1+ standards (●●) and provide 99% protection from harmful UV rays. All lenses are hard coated polycarbonate scratch-resistant unless otherwise noted. Some options meet European (EN166) (●●) standards.

Cortez®

General Specifications

Weight: 23 gm
PD: 68 mm
Bridge: 12 mm
Lens base: 9.5 curve
Lens size diagonal: 70 mm
Lens size vertical: 43 mm
Lens thickness: 2.20 mm
Overall length (lens - tip): 157 mm
Overall width (hinge - hinge): 137 mm
Closest point between temple tips: 73 mm
Closest point between lens: 15.5 mm

Materials

Lens: polycarbonate
Temples: polycarbonate & thermoplastic elastomers (TPE)
Hinge: polycarbonate
Screw: stainless steel
Side shields: polycarbonate
Nosepiece: polycarbonate & polyvinyl chloride (PVC)

Part No.	Lens Markings	Frame Markings
ESB3610S	2 C - 1.2 P 1 F CE	CE P EN166 F
ESB3610ST	2 C - 1.2 P 1 F N CE	CE P EN166 F
ESB3620S	5 -2.5 P 1 F CE	CE P EN166 F
ESB3620ST	5 -2.5 P 1 F N CE	CE P EN166 F

Lens Marking Symbols

Code - field of use

2 or 3: UV filter
5 or 6: Solar filter

Color perception

C: Unimpaired color perception

Protection class

1.2 - 6: Degree of visible light filtration

Optical class

1: High optical quality - no optical distortion

Mechanical Strength

F: Low energy impact, resists a 6 mm, .86 g at 45 m/s

Symbols

P: Manufacturer's mark
N: Filter with anti-fog
CE: Europe standard

Frame Marking Symbols

Symbols

CE: Europe standard
P: Manufacturer's mark
EN166: CE specification for protective eyewear

Mechanical Strength

F: Low energy impact



There's more to see at
PYRAMEXSAFETY.COM

[P] +44 [0] 1635 254220 | [E] info@pyramexeurope.com