

# GL501C5

HPPE | Latex | Crinkle

ANSI/ISEA 105-2016 – CUT A4 | PUNCTURE 4 | ABRASION 4  
EN388: 2016 – 3X42D

Latex crinkle palm coating // 13 gauge HPPE liner //  
Good grip in all conditions

GL501C5 S – 2XL

### Suggested Applications

Material Handling // Glass Handling // General  
Maintenance // Wood Working // Recycling +  
Sanitation Operations

### Glove Breakdown

Type: Dipped Glove
Material: Latex Crinkle
Liner: 13 Gauge HPPE
Cuff: HPPE + Latex Elastic

This product contains components that may be a potential risk to allergic reactions [latex in the wrist cuff]. Do not use in the event of hypersensitivity signs or a known allergy to latex.

### Testing Performance

EN388: 2016 – 3X42D

Abrasion	1	2	3	4		
Circular Blade Cut	1	2	3	4	5	X
Tear	1	2	3	4		
Puncture	1	2	3	4		
Cut TDM-100	A	B	C	D	E	F
Impact Rated	P	F	X			

ANSI/ISEA 105-2016

Cut	1	2	3	4	5	6	7	8	9
Abrasion	1	2	3	4	5	6			
Puncture	1	2	3	4	5				



Latex



Abrasion



Cut



Tear



Puncture



Product markings may vary. Refer to the product sheet for the most current test report results.

### Glove Sizing

The color of the binding around the cuff indicates the glove size.

Small 7	Medium 8	Large 9	X-Large 10	2X-Large 11
------------	-------------	------------	---------------	----------------

All sizes comply with EN 420:2003 for comfort, fit and dexterity. Only wear the correct size for your hand. Gloves that are too loose or too tight will restrict movement and will not provide the optimal level of protection.

### Packaging

Pack: 12 pair
Case: 120 pair
Country of Origin: China