



Nitrile



Abrasion



Tear

# GL601DP

Nylon + Spandex | Nitrile | Micro-Foam  
With Dotted Palm

EN388: 2016 – 4131X

Nitrile micro-foam palm coating // Dotted palm // 15 gauge nylon + spandex liner (silicone free) // Reinforced thumb // Good dexterity // Excellent grip in all conditions

GL601DP S – 2XL

## Suggested Applications

Handling Oily Parts // Warehousing // General Assembly // Automotive Components // Horticulture // General Duty

## Glove Breakdown

Type: Dipped Glove
Material: Nitrile Micro-Foam
Dots: Nitrile Smooth
Liner: 15 Gauge Nylon + Spandex (silicone free)
Cuff: Nylon + Latex Elastic

This product contains components that may be a potential risk to allergic reactions (latex in the wrist cuff). Do not use in the event of hypersensitivity signs or a known allergy to latex.

## Testing Performance

EN388: 2016 – 4131X

Abrasion	1	2	3	4		
Circular Blade Cut	1	2	3	4	5	X
Tear	1	2	3	4		
Puncture	1	2	3	4		
Cut TDM-100	A	B	C	D	E	F
Impact Rated	P	F	X			



## Glove Sizing

The color of the binding around the cuff indicates the glove size.

Small 7	Medium 8	Large 9	X-Large 10	2X-Large 11
------------	-------------	------------	---------------	----------------

All sizes comply with EN 420:2003 for comfort, fit and dexterity. Only wear the correct size for your hand. Gloves that are too loose or too tight will restrict movement and will not provide the optimal level of protection.

## Packaging

Pack: 12 pair
Case: 120 pair
Country of Origin: China