

GL606DPC

HPPE | Nitrile | Micro-Foam
With Dotted Palm

ANSI/ISEA 105-2016 – CUT A3 | ABRASION 6 | PUNCTURE 4
EN388: 2016 – 4X42C

Nitrile micro-foam palm coating // Dotted palm // 18 gauge HPPE liner // Reinforced thumb // Good grip in all conditions

GL606DPC S – 2XL

Suggested Applications

Assembly Line // Furniture Manufacturer // HVAC // Aerospace // Handling Oily Parts // Construction

Glove Breakdown

Type: Dipped Glove
Material: Nitrile Micro-Foam
Dots: Nitrile Smooth
Liner: 18 Gauge HPPE
Cuff: HPPE + Latex Elastic

This product contains components that may be a potential risk to allergic reactions (latex in the wrist cuff). Do not use in the event of hypersensitivity signs or a known allergy to latex.

Testing Performance

EN388: 2016 – 4X42C

Abrasion	1	2	3	4					
Circular Blade Cut	1	2	3	4	5	X			
Tear	1	2	3	4					
Puncture	1	2	3	4					
Cut TDM-100	A	B	C	D	E	F			
Impact Rated	P	F	X						

ANSI/ISEA 105-2016

Cut	1	2	3	4	5	6	7	8	9
Abrasion	1	2	3	4	5	6			
Puncture	1	2	3	4	5				



Nitrile



Abrasion



Cut



Tear



Puncture



Glove Sizing

The color of the binding around the cuff indicates the glove size.

Small	Medium	Large	X-Large	2X-Large
7	8	9	10	11

All sizes comply with EN 420:2003 for comfort, fit and dexterity. Only wear the correct size for your hand. Gloves that are too loose or too tight will restrict movement and will not provide the optimal level of protection.

Packaging

Pack: 12 pair
Case: 120 pair
Country of Origin: China