



PYRAMEX
Perform At Your Peak™

Goliath® ANSI CE CSA AUS



CO-INJECTED
TEMPLES



POLARIZED
OPTION

Co-injected, rubber temples

Part No.	Black Frame
ESB5610D ●●●●	Clear
ESB5620D ●●●●	Gray
ESB5620DT ●●●●	AF Gray H2X
ESB5621D ●●●●	Polarized Gray
ESB5665D ●●●●	Ice Blue Mirror
ESB5665DT ●●●●	AF Ice Blue Mirror
Part No.	White Frame
ESW5620D ●●●●	Gray
ESW5620DT ●●●●	AF Gray H2X
ESW5665D ●●●●	Ice Blue Mirror
ESW5665DT ●●●●	AF Ice Blue Mirror



There's more to see at
PYRAMEXSAFETY.COM

(P) +44 (0) 1635 254220 | (E) info@pyramexeurope.com

All safety eyewear meets ANSI Z87.1+ standards (●) and provide 99% protection from harmful UV rays. All lenses are hard coated polycarbonate scratch-resistant unless otherwise noted. Some options meet European (EN166) (●), Canadian (CSA Z94.3) (●) or Australian (AS/NZS 1337) (●) standards.

Goliath®

General Specifications

Weight: 35 gm
 PD: 68 mm
 Bridge: 13.8 mm
 Lens base: 8 curve
 Lens size diagonal: 62.6 mm
 Lens size vertical: 37.6 mm
 Lens thickness: 2.3 mm
 Overall length (lens - tip): 163.5 mm
 Overall width (hinge - hinge): 131 mm
 Closest point between temple tips: 96.5 mm
 Closest point between lens: 18 mm

Materials

Lens: polycarbonate
 Temples: polycarbonate & thermoplastic rubbers (TPR)
 Hinge: polycarbonate
 Screw: stainless steel
 Side shields: polycarbonate

Part No.	Lens Markings	Frame Markings
ESB5610D	2 C - 1.2 P 1 F CE	CE P EN166 F
ESB5620D	5 -2.5 P 1 F CE	CE P EN166 F
ESB5620DT	5 -2.5 P 1 F N CE	CE P EN166 F
ESB5621D	5 -3.1 P 1 F CE	CE P EN166 F
ESB5665D	5 -3.1 P 1 F CE	CE P EN166 F
ESB5665DT	5 -3.1 P 1 F N CE	CE P EN166 F
ESW5620D	5 -2.5 P 1 F CE	CE P EN166 F
ESW5620DT	5 -2.5 P 1 F N CE	CE P EN166 F
ESW5665D	5 -3.1 P 1 F CE	CE P EN166 F
ESW5665DT	5 -3.1 P 1 F N CE	CE P EN166 F

Lens Marking Symbols

Code - field of use

2 or 3: UV filter
 5 or 6: Solar filter

Color perception

C: Unimpaired color perception

Protection class

1.2 - 6: Degree of visible light filtration

Optical class

1: High optical quality - no optical distortion

Mechanical Strength

F: Low energy impact, resists a 6 mm, .86 g at 45 m/s

Symbols

P: Manufacturer's mark
 N: Filter with anti-fog
 CE: Europe standard

Frame Marking Symbols

Symbols

CE: Europe standard
 P: Manufacturer's mark
 EN166: CE specification for protective eyewear

Mechanical Strength

F: Low energy impact



There's more to see at
PYRAMEXSAFETY.COM

(P) +44 (0) 1635 254220 | (E) info@pyramexeurope.com