

3M[™] Body Repair Tools

3M™ Mini File Belt Sander and File Belt Sander

3M[™] File Belt Sanders allow technicians to access hard-to-reach areas and are great for spot weld removal, deburring, cleaning, and finishing. Remove spot welds cleanly and quickly with 3M[™] Cubitron[™] II File Belts — replacing the need for expensive drills and bits. Adjustable arm for user comfort and multiple applications. Available in 13" and 18" sizes.

Part No.	Belt Size in (mm)	Max RPM	Weight lb (kg)	Height in (mm)	Length in (mm)	Motor hp (W)	
Belt Speed: 4100 SFPM (1250 SMPM)							
33573	3/8 × 13 (10 × 330)	17.000	2.07 (0.94)	2.87 (73)	12.50 (320)	0.65 (485)	
33575	1/2 × 18 (13 × 457)	17,000	2.16 (0.98)		15.15 (385)		

3M™ Cut-Off Wheel Tools

3M™ Cut-Off Wheel Tools deliver the performance you need when working with tough automotive substrates. When paired with 3M™ Cubitron™ II Cut-Off Wheels, technicians can even slice through high-strength steel and aluminum with clean, straight lines and minimal effort. Power with a Cubitron II cut-off wheel for a cleaner cut that runs cooler. Compact design with built-in safety features for easy handling. Featuring a light-weight composite body for greater user comfort. Available in 3" and 4" sizes.

Part No.	Wheel Size in (mm)	Max RPM	Thread Size	Weight lb (kg)	Height in (mm)	Length in (mm)	Motor hp (W)
ALWAYS USE WITH GUARD							
33579	3 (75)	00.000	1/4" – 28	1.91 (0.87)	3.14 (79.6)	7.73 (196)	0.70 (522)
33581	4 (100)	20,000		2.00 (0.91)	3.42 (86.9)		

3M™ Pistol Grip Disc Sander

Light-weight tool with the power to grind welds. Conveniently sized to access small and hard-to-reach areas. Perfect for grinding and sanding applications with our 3M™ Cubitron™ II Fibre Roloc™ Discs. Variable speed adjustment for optimal finish.

Part No.	Max RPM	Thread Size	Weight lb (kg)	Height in (mm)	Length in (mm)	Motor hp (W)	
Use with 2" (50mm) and 3" (75mm) discs*							
33577	18,000	1/4" – 20	1.76 (0.8)	2.05 (52)	7.50 (189)	0.45 (336)	

^{*}Tool includes a 2" (50mm) and 3" (75mm) 3M™ Roloc™ Disc Pad. For discs, see page 6-7.







3M[™] Cubitron[™] II File Belt 786F, 10mm x 330mm, 36+, 33437



3M™ Cubitron™ II Cut-Off Wheel, 75mm x 1mm x 9.53mm, 33456



3M[™] Cubitron[™] II Roloc[™] Fibre Disc 786C, 75mm, 36+, 33389